

INDUSTRIAL OFF-ROAD UTILITY VEHICLES



Zeal Motor Inc. 90 Blvd de l'Aeroport, Bromont Quebec, Canada J2L 1S9

579.319.0060 sales@zealmotor.com

WWW.FATTRUCK.COM



SPECIFICATIONS

Performance

2200 lbs (1000 kg) Pavload 8 (2 front+ 6 rear) Passengers capacity Maximum speed on land 25 (40 km/h) Maximum speed on water 3.1 mph (5 km/h) Maximum uphill & downhill 35°/70% Maximum sidehill 22°/40% Turning radius 00

Shipping weight 5400 lb (2443 kg) Ground pressure fully loaded 1,6 lb/po² (0,11 kg/cm²)

Safety features

ROPS ISO 3471 EPA TIFR 4 Final

Brakes Automatic safety brake

Dimensions

Height 101 in (2565 mm) 146,5 in (3720 mm) Length Width 100 in (2540 mm) Ground clearance 20,7 in (526 mm)

Controls

Controller Microprocessor Steering lovstick Color display Display

Engine

Make Caterpillar Model C2.2 Turbo diesel **Emission standards** Tier 4 final (no DPF)

Number of cylinders 4 cylinders Displacement 135 po³ (2,22 L) Horsepower @ 2800 RPM 67 hp (50 kW) Torque @ 1400 RPM 153 lb-pi (208 N-m)

Cooling System Liquid cooled

Electrical

12 V Voltage 85 A Alternator capacity 960 CCA Battery capacity Battery type AGM

Transmission

Hydrostatic Type

Carbon fiber synchronous belts Final drive

Brakes

Brakes Positive deceleration through hydrostatic transmission

Brake disc applied pressure released Park brakes

Tires

Front & Rear FAT TRUCK™ LGP 1640 x 640 x 610 Pressure 0,5 to 4 psi (0,035 to 0,28 kg/cm²) Pressure control Preset automatic pressure control

Fuel System

Capacity

18.5 US Gal (70 L)

Average fuel autonomy 10 h

Standard equipment

Doors Lockable

2 front seats with 3-points seat belts Operator seats

Windows Sliding side windows

Front, brakes, position, flashers, dome Lights

Heating Heater/Defroster

Electric Horn

Retractable ladders with grab handles Ingress

Standard color Red Fire extinguisher 2.5 lbs. ABC

First aid kit Lockable fuel cap Front and rear bumpers Operator & Maintenance manual Spare Parts catalog (on USB flash drive)

Cab Options

Custom color Air conditioning Basic brush guard Additional Brush guard(s) Roof rack with rear ladder

Exterior mirrors

Rear seats with 2-points safety belts

3-points seat belts

Directional light with remote control

Front and rear light bar

Bluetooth radio with speakers

LED beacon light Back up camera Back-up alarm Inclinometer Roof hatch

Options

Vehicle remote control

Winch

Additional battery Cold weather Kit

Hitch

Trailer

Front and rear D-rings

Winch ready 12V front & rear

Side LED bar Wheel Pods™ Amphibious trailer

Warranty

Limited 1 year / 1000 hours (Which ever comes first)





