



SK 170MX Excavator



SK170MX Excavator

Engine	C4.4 Tier IV Final
Engine Power	129.5 kW (173.5hp)
Weight	15,875 kg 35,000lbs
Std U/C	46 shoe 28" Triple Grouser
Optional U/C	44 shoe 38" Single Grouser

SK 170MX Excavator

Specifications

Capacities:

Hydraulic 26 gallons
Fuel 66 gallons
DEF 19L DEF tank 12V

Hydraulic System:

Circuit Type Closed Loop
High Flow 50 GPM @ 2200 RPM
Max Pressure 5500 PSI

Std. Flow Aux 25 GPM 1900 RPM
Std. Flow 3500 PSI

Dimensions:

Height 9'5"
Width 102" (24" Grouser)
105" (28" Grouser)
Length: 25.25"
Tracks Options 24", 28", 38"
Weight: 35,000lbs w/28" grouser, Mulcher head

Filtration: High Pressure Filters
Remote Charge Filter
Surge Protection
1 Gallon Accumulator

Cooling: Heavy Duty Radiator / Oil Coolers
Extra Large Intake Air
Roof Louvers, reversing Fans,
Removable Debris Screens

Enclosure: Robust Engine/Service Doors

Controls: Std Cab layout with engine
display and hydraulic diagnostics.



Optional 38" Single Grouser



26955 Airport Road
Punta Gorda, Florida 33982
1 800 446 9858
1 941 505 7800
www.supertrak.com